# TS2GJF2A

**2GB USB2.0 JetFlash™2A**

## Description

TS2GJF2A is a 2GB USB Flash Drive with 1pcs of 2Gx8 (or 2pcs of 1Gx8) Flash Memory assembled on printed circuit board.

## Outline




## Features

- Color: Silver
- USB Interface: Compliant with USB specification 2.0.
- Security Function: Password protection provided
- Boot-Up Function: Support USB-ZIP/USB-HDD boot-up mode supported
- PC-Lock Function: Makes JF2A the key to your computer
- No external power or battery needed
- LED indicates the usage status.

## Dimensions

| Side | Millimeters | Inches |
|---|---|---|
| A | 75 ± 1.00 | 2.95 ± 0.04 |
| B | 11 ± 1.00 | 0.43 ± 0.04 |
| C | 25 ± 1.00 | 0.98 ± 0.04 |

## Block Diagram

- **With 1 pcs of 2Gx8 Flash Memory**




- **With 2 pcs of 1Gx8 Flash Memory**



## Pinouts

| Pin No. | Pin Name |
|---|---|
| 01 | VCC |
| 02 | USB- |
| 03 | USB+ |
| 04 | VSS |

## Pin Identification

| Symbol | Function |
|---|---|
| USB- | USB differential signal: |
| USB+ | The pairs are used to transmit Data/Address/Command |
| VSS | Ground |
| VCC | USB power input |

## Specifications

| | |
|---|---|
| Storage Capacity | 2GB |
| Data Retention | 10 years |
| Erase Cycles | >100,000 times |
| Connector Durability | 10,000 times |
| System Performance | Read: 12MB/sec (max.), Write: 8MB/sec (max.) |
| Power Supply | DC 5V±10% via the USB port |
| Temperature Range | Operation: 0-70°C, Non-Operating: -40°C-85°C |
| Certificates | CE, FCC, BSMI |

## Absolute Maximum Ratings

| Symbol | Parameter | Rating | Unit |
|---|---|---|---|
| $V_{CC}$ | Power Supply | 4.5 to 5.5 | V |
| $V_{IN}$ | Input Voltage | 3 to 3.6 | V |

## DC Characteristics:

| Symbol | Parameter | Min. | Typ. | Max. | Units |
|---|---|---|---|---|---|
| $I_{IL}$ | Input Leakage Current (No pull-up or pull-down) | -10 | | 10 | μA |
| $I_{OZ}$ | Tri-State Leakage Current | -10 | | 10 | μA |
| $V_{IL}$ | Input Low Voltage | | | 0.8 | V |
| $V_{IH}$ | Input High Voltage | 2.0 | | | V |
| $V_{OL}$ | Output Low Voltage ($I_{OL}$=4mA) | | | 0.4 | V |
| $V_{OH}$ | Output High Voltage ($I_{OH}$=4mA) | 2.4 | | | V |
| Rt | Input pull-up/down resistance ($V_{IL}$=0V or $V_{IH}$= $V_{CC}$) | 40 | 75 | 190 | KΩ |
| $I_{ACT}$ | Active Current | | | 73 | mA |
| $I_{SLP}$ | Sleep Current | | | 120 | μA |

## Recommended Operating Conditions

| Symbol | Parameter | Min. | Typ. | Max. | Units |
|---|---|---|---|---|---|
| $V_{CC}$ | Power Supply Voltage | 4.5 | 5 | 5.5 | V |
| $V_{IN}$ | Input Voltage | 3 | 3.3 | 3.6 | V |
| $V_{CC18}$ | Internal Power Supply | 1.62 | 1.8 | 1.98 | V |

Above technical information is based on industry standard data and tested to be reliable. However, Transcend makes no warranty, either expressed or implied, as to its accuracy and assumes no liability in connection with the use of this product. Transcend reserves the right to make changes in specifications at any time without prior notice.